

JVC-

100

50G

		HG3450G
	BIOS	UEFI
		2xDDR5 , SODIMM,max 64G
		/ /Win10/Win11 OS
I/O	USB	4xUSB3.0, 1xUSB2.0 type A for USB Dongle
	COM	2xRS232/422/485 6xRS232
	GPIO	2xDB9 8bit GPIO
	LED	1xPower, 1xHDD
	PCIe/M.2/Mini-PCIe	1 M.2 Key-E for Wifi/BT 1x M.2 B-key 3052 Micro SIM 5G
	Interface	1xVGA, 1xHDMI
	Storage Device	2 x SATA3.0, 1xM.2 SSD NVME(PCIe5.0 X4)
	Audio IC	SN6186
	Audio Interface	1xMic-in, 1xLine-out
	LAN IC	3xRTL8111M-CG, 1xYT8531H-CA
	Interface	4xRJ45
	Power Input	12V, DC-in,
	Power Interface	2-Pole Phoenix DC plug in
	Watchdog Timer	1 to 255 sec./min. per step
	TCM	Z32H330TC TCM2.0
	Dimensions (L*W*H)	200*205*89 mm
	Mounting	Desk/Wall-mounting
	Operating Temp.	-10 ~60
	Storage Temp.	-40 ~85
	Humidity	95%@40°C non-condensing
	Shock	With SSD: 15G, IEC 60068-2-27, half sine, 11ms duration
	Vibration	With SSD:2Grms, IEC 60068-2-64, random 5~500Hz 1 hr/axis



JVC-9100

			DIMM	LAN	USB 3.0	COM	GPIO	SATA 3.0	M.2 SSD
JVC-9100	HG3450G	2	2	4	4	8	2	2	1



JVC-9100	JVC-9100	1
NA	&	1